

Kodak

i1200 Plus Series Scanners



Meet all your workgroup needs with an easy-to-use scanner that fits anywhere

Small, powerful and packed with features and benefits, the **Kodak** i1210 Plus and i1220 Plus Scanners deliver on your desktop scanning needs. They can auto-feed almost anything at speeds up to 45 pages per minute, including documents as small as an identification card or as long as 863 mm (34 in.).

All the ease of use and versatility you need

Our Smart Touch feature enables you to easily select the right scan settings and applications for the job. With the touch of a button, scan documents to:

- **Microsoft SharePoint**
- File and storage
- E-mail, including Web e-mail clients such as **Gmail, Yahoo!** and **Hotmail**
- Printers
- Other desktop applications that support TIFF, JPEG, RTF, BMP, PDF and searchable PDF

In addition, these powerful scanners have a unique tilt-and-scan feature that allows you to select the best scanning position for the job:

- Flat with trays extended for higher-volume batch scanning
- Fully upright with the input tray folded down for transaction scanning

There are also optional “tethered” flatbed accessories in A3 and A4 sizes for more convenience and flexibility. Just connect either, and you can scan A3 documents at up to 600 dpi and A4 documents at up to 1,200 dpi. Then just unplug and store the flatbed. It’s that easy!

Get exceptional image quality

It starts with 600 dpi optical resolution for razor-sharp images. But we didn’t stop there. These compact machines feature our latest Perfect Page technology, which delivers imaging benefits such as:

- Streak filtering, to improve the appearance of images and reduce the need for cleaning
- Image hole fill, for cleaner-looking images from hole-punched documents
- Sharpness filtering, which enhances overall image clarity

It all adds up to outstanding image quality that’s virtually automatic. No need for rescans!

Enjoy unique value

With all this capability, affordable pricing and the peace of mind that comes with **Kodak** Service & Support, the i1210 Plus and i1220 Plus Scanners deliver an extraordinary combination of performance and value.



KONICA MINOLTA

COUNT ON **KONICA MINOLTA**

Authorized Reseller of **Kodak** Document Imaging Products

Kodak i1200 Plus Series Scanners

Specifications

Recommended Daily Volume	Up to 3,000 pages per day
Throughput Speeds (portrait, letter size)	Bitonal/grayscale: Up to 45 ppm/90 ipm at 200 dpi Color: Up to 30 ppm/60 ipm at 200 dpi (Throughput speeds may vary depending on your choice of driver, application software, operating system and PC.)
Scanning Technology	i1210 Plus: Single CCD; i1220 Plus: Dual CCD; Grayscale output bit depth is 256 levels (8 bits) Color capture bit depth is 48 bits (16 x 3); Color output bit depth is 24 bits (8 x 3)
Optical Resolution	600 dpi (1200 dpi A4 flatbed accessory)
Illumination	Dual fluorescent (cold cathode)
Output Resolution	75, 100, 150, 200, 240, 300, 400, 600 and 1200 dpi
Max./Min. Document Size	215 mm x 863 mm (8.5 in. x 34 in.)/50 mm x 63.5 mm (2 in. x 2.5 in.)
Paper Thickness and Weight	34-413 g/m ² (9-110 lb.) paper; ID card thickness: up to 1.25 mm (0.05 in.)
Feeder	Up to 75 sheets of 75 g/m ² (20 lb.) paper, handles small documents such as ID cards, embossed cards and insurance cards
Multi-feed Detection	With ultrasonic technology
Connectivity	USB 2.0 (cable included)
Bundled Software	TWAIN, ISIS, WIA Drivers; Kodak Capture Desktop Software, Smart Touch; Nuance ScanSoft PaperPort and OmniPage. Linux SANE and TWAIN Drivers available from www.kodak.com/go/scanonlinux .
Imaging Features (in the scanner)	Perfect Page Scanning; iThresholding; adaptive threshold processing; deskew; autocrop; relative cropping; aggressive cropping; electronic color dropout; dual stream scanning; interactive color, brightness and contrast adjustment; automatic orientation; automatic color detection; background color smoothing; image edge fill; image merge; content based blank page detection; streak filtering; image hole fill; sharpness filter
File Format Outputs	Single and multi-page TIFF, JPEG, RTF, BMP, PDF, searchable PDF
Warranty (US and Canada)	One-year warranty
Accessories	Kodak white imaging background accessory (front); Kodak A3 Flatbed (black background) Accessory with 1.8-meter (6 ft.) cable; Kodak A4 Flatbed (white background) Accessory with 1.8-meter (6 ft.) cable; Optional A4 flatbed black imaging background accessory
Electrical Requirements	100-240 V (International); 50-60 Hz
Power Consumption	Scanner: Off mode: <4 watts; Running: <35 watts Scanner with A3 Flatbed: Off mode: ≤6 watts; Running: <65 watts Scanner with A4 Flatbed: Off mode: ≤6 watts; Running: <57 watts
Environmental Factors	Energy Star qualified scanners, Operating temperature: 10-35° C (50-95° F), Operating humidity: 15% to 76% RH
Acoustical Noise (operator position sound pressure level)	Off mode: <30 dB(A) Operating mode: <58 dB(A)
Recommended PC Configuration	For documents up to 660 mm (26 in.) long at 400 dpi: Intel Core2 , 2 GHz Duo Processor or equivalent, 2 GB RAM For longer documents/higher resolutions: Intel Core2 , 2 GHz Duo Processor or equivalent, 4 GB RAM Note: for optimal performance when using a PC running the Windows 7 operating system, at least 3 GB RAM is recommended.
Supported Operating Systems	Windows XP SP2 and SP3 (32-bit), Windows XP x64 edition SP2, Windows Vista SP1 (32-bit and 64-bit), Windows 7 (32-bit and 64-bit), Windows 2003 Server and 2008 Server x64 Editions, Linux Ubuntu 8.04, Fedora 9 , SUSE 11
Approvals and Product Certifications	AS/NZS 3548 Class B (C-Tick Mark), CAN/CSA-C22.2 No. 60950-1-03 (C-UL Mark), Canada ICES-003 Issue 3 (Class B), GB4943, GB9254 (Class B), GB 17625.1 Harmonics (CCC "S&E" Mark), EN 55022 ITE Emissions (Class B), EN 61000-3-3 Flicker, EN 55024 ITE Immunity (CE Mark), EN 60950 (TUV GS Mark), IEC 60950, CISPR 22 (Class B), VCCI (Class B), CNS 13438 (Class B), CNS 14336, (BSMI Mark), UL 60950-1 (UL Mark), CFR 47 Part 15 Subpart B (FCC Class B), Argentina S-Mark
Consumables Available	Feed module, separation module, feed rollers, roller cleaning pads, Staticide Wipes
Dimensions	Weight: i1210 Plus: 5.2 kg (11.5 lbs.), i1220 Plus: 5.5 kg (12 lbs.) Depth: 162 mm (6.3 in.) not including input tray and output tray Width: 330 mm (13 in.) Height: 246 mm (9.7 in.) not including input tray

To learn more:

www.kodak.com/go/i1200Plus

Printed using Kodak Technologies.

Eastman Kodak Company
343 State Street, Rochester, NY 14650
1-800-944-6171

Kodak Canada, Inc.
Toronto, Ontario M9R 0A1
1-800-465-6325

©Kodak, 2010. Kodak is a trademark of Kodak.
Specifications are subject to change without notice.



Kodak

It's time for you **AND** Kodak



KONICA MINOLTA

Authorized Reseller of **Kodak** Document Imaging Products

**KONICA MINOLTA
BUSINESS SOLUTIONS U.S.A., INC.**
100 Williams Drive
Ramsey, NJ 07446
www.CountOnKonicaMinolta.com
www.kmbs.konicaminolta.us